

# Montana Specification



## COMPOSITION

Construction	ISO2424	Tufted 1/10th Loop Pile
Pile Fibre	ISO2076	100% Solution Dyed Polypropylene
Primary Backing	ISO2424	Non-woven Polyester
Secondary Backing	ISO2424	Bitumen with glass fibre 3kg/m <sup>2</sup>
Pile Height	ISO1766	4.5 mm ± 0.5mm
Total Height	ISO1765	5.9 mm ±0.5mm
Pile Weight	ISO1958	395 gr/m <sup>2</sup> ± 5%
Total Weight	ISO8543	4140 gr/m <sup>2</sup> ± 10%
Pile Density	ISO1763	192,000 tufts/m <sup>2</sup> ± 5%
Tile Size	EN994	50 x 50 cm
Tiles per Box		20 tiles per box (5m <sup>2</sup> )

## CLASSIFICATION

Flammability (Fire Spread EN13501)	ISO11925	Fs ≤ 150mm within 20 seconds
Flammability (Radiant Panel EN13501)	ISO9239	D <sub>fl</sub> -S1
Flammability (Hot Metal Nut)	BS4790	Low radius effects of ignition
Wear Resistance (Castor Chair Test)	ISO4918	Matting Protectors Recommended
Electrical Vertical Resistance	ISO10965	Pass ≤ 10 <sup>9</sup> Ω
Electrostatic Propensity (Stroll Test)	ISO6356	Pass <2.0kV
Slip Resistance	EN13893	DS
Dimensional Stability	EN986	Pass <0.2%
Acoustic Impact Noise Reduction	ISO717	24dB
Sound Absorption	ISO354	500Hz-0.07as, 1000Hz-0.19as, 2000Hz-0.28as, 4000Hz-0.32as
Colour Fastness – Light (CIELAB)	ISO105	≥6
Colour Fastness – Rubbing (CIELAB)	ISO105	≥5
Colour Fastness – Water (CIELAB)	ISO105	≥5
Classification for Use	ISO10874	Class 31 Commercial Moderate
Luxury Class Rating	EN1307	LC1


## WARRANTY

5 Year Wear Warranty

## CERTIFICATION



## INSTALLATION



© The Floor Hub. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available on request.

The Floor Hub HQ & Trade Bar, No 3, 14 Greycaine Road, Watford, Herts. WD24 7GP  
 The Floor Hub Showroom, The Vault, 8-11 St John's Lane, Clerkenwell, London. EC1M 4BF  
 Tel: 01923 211151 Email: hello@thefloorhub.co.uk  
 www.thefloorhub.co.uk