

Lagoon Specification



COMPOSITION

Construction	ISO2424	Tufted 1/10th Cut & Loop Pile
Pile Fibre	ISO2076	ECONYL 100% Regenerated Space Dyed Nylon
Primary Backing	ISO2424	Non-woven Polyester
Secondary Backing	ISO2424	Bitumen with glass fibre 3kg/m ²
Pile Height	ISO1766	3.4 mm ± 0.5mm
Total Height	ISO1765	6.5 mm ± 0.5mm
Pile Weight	ISO1958	800 gr/m ² ± 5%
Total Weight	ISO8543	4400 gr/m ² ± 10%
Pile Density	ISO1763	206,000 tufts/m ² ± 5%
Tile Size	EN994	50 x 50 cm
Tiles per Box		20 tiles per box (5m ²)


CLASSIFICATION

Flammability (Fire Spread EN13501)	ISO11925	Fs ≤ 150mm within 20 seconds
Flammability (Radiant Panel EN13501)	ISO9239	B _{fl} -S1
Flammability (Hot Metal Nut)	BS4790	Low radius effects of ignition
Wear Resistance (Castor Chair Test)	ISO4918	Pass ≥ 2.4 (A – Continuous Use)
Electrical Vertical Resistance	ISO10965	Pass ≤ 10 ⁹ Ω
Electrostatic Propensity (Stroll Test)	ISO6356	Pass <2.0kV
Slip Resistance	EN13893	DS
Dimensional Stability	EN986	Pass <0.2%
Acoustic Impact Noise Reduction	ISO717	23dB
Sound Absorption	ISO354	500Hz-0.06as, 1000Hz-0.16as, 2000Hz-0.29as, 4000Hz-0.36as
Colour Fastness – Light (CIELAB)	ISO105	≥7
Colour Fastness – Rubbing (CIELAB)	ISO105	≥4
Colour Fastness – Water (CIELAB)	ISO105	≥4
Classification for Use	ISO10874	Class 32 Commercial General
Luxury Class Rating	EN1307	LC2

ENVIRONMENTAL

BREEAM A+ Rating


CERTIFICATION



WARRANTY

10 Year Wear Warranty

INSTALLATION



© The Floor Hub. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available on request.

The Floor Hub HQ & Trade Bar, No 3, 14 Greycaine Road, Watford, Herts. WD24 7GP
 The Floor Hub Showroom, The Vault, 8-11 St John's Lane, Clerkenwell, London. EC1M 4BF
 Tel: 01923 211151 Email: hello@thefloorhub.co.uk
 www.thefloorhub.co.uk